TIANKI (CHINA) ENTERPRISE CO., LTD.



Plant:Nanyang ETDZ, Xiaoshan District Hangzhou China

Tel:+86-571-82778679 Fax:+86-571-82778609 Email:sales@tkechem.com

TECHNICAL DATA SHEET

Product Description:

Fast Yellow 10G		
Pigment Yellow 3		
11710		
6486-23-3		
229-355-1		
Mono azo		

Technical Properties:

azo pigment, greenish shade yellow pigment, having very good resistance

Application:

Recommend: water based decorative paint and industrial paint

Physical Properties

Density(g/cm3)	1.6
Moisture (%)	≤2.0
Water Soluble Matter	≤1.5
Oil Absorption (ml / 100g)	25-35
Electric conductivity (us/cm)	≤500
Fineness(80mesh)	≤5.0
PH value	6.0-7.0

Fastness Properties (5=Excellent, 1=Poor)

Acid Resistance	5	Soap Resistance	-
Alkali Resistance	5	Bleeding Resistance	4
Alcohol Resistance	5	Migration Resistance	-
Ester Resistance	3	Heat Resistance (°C)	160
Benzene Resistance	3	Light	6
Ketone Resistance	-	Fastness(8=Excellent)	

Note: The above information is provided as guidelines for your reference only. The accurate effects should base on the test results in laboratory.